




Materials and colours opaline glass cylinder with brass black varnished stem

Light source LED bulb G4 12V DC 1x1,5W / energy class A+ / lumen 150 / K 2700 / CRI 85 / protection grade IP65

Power supply 12V DC transformer not included

Dimensions



cylinder with holder
 Ø 1,5 x H 21 cm
 H tot. 65 cm (cable 255 cm)
 H tot. 80 cm (cable 240 cm)
 H tot. 110 cm (cable 210 cm)
 H tot. 140 cm (cable 180 cm)

Order code

SYS65	H 65 cm
SYS80	H 80 cm
SYS110	H 110 cm
SYS140	H 140 cm

Accessories for gel box system

ED6	driver 10W 12V DC 220-240V IP67 not dimmable (max 6 lamps)
MB1	mini gel box IP68 (max 2 connections, connector included)
MB2	mini gel box IP68 (max 6 connections, connector included)
KP1	extension kit 5 mt with mini gel box IP68 (max 1 lamp)

Accessories for quick connectors system

ED6CR	driver 10W 12V DC 220-240V IP67 not dimmable with quick connectors (max 6 lamps)
CRM	multiple quick connector IP68 - 1 IN & 5 OUT (max 5 connections)
CRS	single quick connector IN IP68
KP2	extension kit 5 mt with quick connectors IP68 (max 1 lamp)