

Floor lamp with body in extruded aluminum, heads and base in die-casted aluminum, diffusers in opal and transparent metacrylate. Structure painted in matt white or black. The uplight LED source provides a warm and diffused flood, while the back LED creates an indirect ambient lighting.





LED 2700K

		_
.amping		
ource	LINEAR LED + LED BOARD	
otal power	41 + 16 W	
mission	UP + BACK, INDIRECT	
witching	DOUBLE DIMMING, PUSH ON BOARD	
ension	120V	
Color temperature	2700K	72.8
yp cri	83	7
nergy class	В	
class	20	
imensions	4.7 X 3.9 X 72.8	
laterials	aluminum + PC	
_		
Codes	Structure Diffuser	
RU LNN 25	black	_
vhite		
	titon grou	

white	
TRU LDD 25	titan grey
white	
TRU LWW 25	white
white	
TRU LGG 25	gold painted
white	
Net lamp weight	19.8 lbs

Package 1

Dimensions				
Gross weight				

11 X 10.2 X 7.9 17.6 lbs

Package 2

Dimensions Gross weight 8.7 X 67 X 75.2 8.8 lbs



LED 3000K

Lamping	
Source	LINEAR LED + LED BOARD
Total power	41+16 W
Emission	UP + BACK, INDIRECT
Switching	DOUBLE DIMMING, PUSH ON BOARD
Tension	120V
Color temperature	3000K
Luminous flux	4080lm + 2660lm
Тур сгі	83
Energy class	A+
p class	20
Dimensions	4.7 X 3.9 X 72.8
Materials	aluminum + PC
Notes	cable length 10.8', push on board

Codes	Structure	Diffuser
TRU LDD 24	titan grey	
white		
TRU LGG 24	painted gold	
white		
TRU LWW 24	white	
white		
TRU LNN 24	black	
white		
Net lamp weight	19.8 lbs	

Package 1

Dimensions Gross weight 11 X 10.2 X 7.9 17.6 lbs

Package 2

Dimensions Gross weight 8.7 X 67 X 75.2 8.8 lbs | | 4.7

| | 3.9