Koto Single

astro

General

Location:	Interior
Class:	cULus (Class I)
Location Rating:	Dry
Driver Required:	Mains 120V
Installation Orientation:	Ceiling Mount
Fitting Method:	4" Octagon Box
Main Material:	Metal - Aluminium
Dimensions (mm):	H: 166 W: 110 D: 110 Ø: 110
Dimensions (inch):	H: 6.54 W: 4.33 D: 4.33 Ø: 4.33
Cut Out Hole (mm/inch):	-
Recess Depth (mm/inch):	-
Fire Rating:	-
Cable Length (mm/inch):	-
Gross Weight (lb):	1.36
Ada Compliant:	Yes - if installed in compliance with ADA 307.2, 307.4
Ic Rating:	-

CODE: 1478017
FINISH: MATT BLACK

CODE: 1478023
FINISH: MATT WHITE

Lamp

Light Source:	GU10
Wattage:	20W Max
Recommended Lamp:	6W Max LED GU10
Lamp Included:	No
Maximum Lamp Length (mm/inch):	53/2.09
Luminous Flux (lm):	Lamp Dependent
Colour Temp (K):	Lamp Dependent
Cri (Ra):	Lamp Dependent
Macadam Ellipse:	Lamp Dependent
Tilt Adjustable Angle (°):	90
Rotation Adjustable Angle (°):	330
Average Lifetime (hrs):	Lamp Dependent
Beam Angle (°):	Lamp Dependent

Electrical

Switched:	No
Dimmable:	Yes
Dimming Method:	Lamp Dependent
Supply Frequency (Hz):	-
Driver/Ballast Voltage (V):	-
Driver Average Lifetime (hrs):	-
Efficacy (lm/W):	Lamp Dependent

Additional Information:

Shade Included:	-
Shade/Diffuser Material:	-
Shade/Diffuser Finish:	-
F Mark:	Suitable for mounting on flammable materials

Product Elevations

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

astro

Ø110mm / 4.33"

20mm / 0.79"

Ø89mm / 3.5"

166mm / 6.54"

90°

UL CERTIFIED