MASCALI ROUND LED

astro

GENERAL

LOCATION: CLASS: LOCATION RATING: DRIVER REQUIRED: INSTALLATION ORIENTATION: FITTING METHOD: MAIN MATERIAL: DIMENSIONS (mm): DIMENSIONS (mm): CUT OUT HOLE (mm/inch): RECESS DEPTH (mm/inch): FIRE RATING: CABLE LENGTH (mm/inch): GROSS WEIGHT (lb): ADA COMPLIANT: Bathroom cULus (Class 1) Damp Mains 120V Wall Mount - Horizontal 1/2in Stub Mount & 4" Octagon Box Metal - Mild Steel D: 278 Ø:215 D: 10.94 Ø: 8.46 --3.92

Yes - if installed in compliance with ADA §307.2, 308, 309.3, 309.4



CODE: 1373014 FINISH: MATT BLACK



CODE: 1373015 FINISH: POLISHED CHROME

IC RATING:

LAMP

| LIGHT SOURCE: | LED Strip |
|--------------------------------|----------------|
| WATTAGE: | 5.6W |
| LAMP INCLUDED: | Yes (Integral) |
| MAXIMUM LAMP LENGTH (mm/inch): | - |
| LUMINOUS FLUX (Im): | To Be Advised |
| COLOUR TEMP (K): | 3000 |
| CRI (Ra): | 90 |
| MACADAM ELLIPSE: | 2900-3000K |
| TILT ADJUSTABLE ANGLE (°): | 65 |
| ROTATION ADJUSTABLE ANGLE (°): | 180 |
| LIFETIME (hrs): | 53000 |
| BEAM ANGLE (°): | 115.7 |

ELECTRICAL

| SWITCHED: | Yes |
|-----------------------------|---------|
| DIMMABLE: | No |
| DIMMING METHOD: | - |
| SUPPLY FREQUENCY (Hz): | 50/60 |
| DRIVER/BALLAST VOLTAGE (V): | 100-240 |
| DRIVER LIFETIME (hrs): | 35000 |
| EFFICACY (Im/W): | 22 |
| | |

ADDITIONAL INFORMATION:

SHADE INCLUDED: SHADE / DIFFUSER MATERIAL: SHADE / DIFFUSER FINISH F MARK:

Glass Mirror Finish Suitable for mounting on flammable materials TO MAINTAIN THIS PRODUCT TO ITS BEST CONDITION, PLEASE VIEW OUR CARE AND CLEANING GUIDELINES ON THE SUPPORT SECTION OF THE ASTRO WEBSITE.

ASTRO® IS A REGISTERED TRADEMARK OF ASTRO LIGHTING LIMITED. ASTRO LIGHTING'S FIXTURE DESIGNS AND IMAGERY ARE PROTECTED UNDER U.S. AND INTERNATIONAL INTELLECTUAL PROPERTY LAWS, AND ALL RIGHTS TO SUCH DESIGNS AND IMAGERY ARE EXPRESSLY RESERVED.

PRODUCT ELEVATIONS

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.





