


120/240V LED Driver - 4W



WH-L03U-12V

PRIMARY: AC 100 - 240V, 120mA, 50/60Hz

SECONDARY: Max. 12V DC (4.2w max.)

LAMPING: 1w LED lamps: 1-3
1.5w LED lamps: 1-2
2.3w ring LED lamps: 1

DIMMING: Non-dimmable

NOTES: Constant voltage
Class 2 power unit
For LED lamps only

DIMENSION: 43mm (1.7") x 41mm (1.6") x 22mm (0.8")

DESIGNATION:




SELV-equivalent



ta: 50°C
tc: 75°C

120/240V LED Driver - 8W



WH-L07U-12V

PRIMARY: AC 100 - 240V, 170mA, 50/60Hz

SECONDARY: Max. 12V DC (8.4w max.)

LAMPING: 1w LED lamps: 1-7
1.5w LED lamps: 1-5
2.3w ring LED lamps: 1-3

DIMMING: Non-dimmable

NOTES: Constant voltage
Class 2 power unit
For LED lamps only

DIMENSION: 65mm (2.5") x 35mm (1.3") x 28mm (1.1")

DESIGNATION:




SELV-equivalent



ta: 50°C
tc: 75°C

120/240V LED Driver - 24W



WH-L24U-12V

PRIMARY: AC 100 - 240V, 300mA, 60Hz

SECONDARY: Max. 12V DC (24w max.)

LAMPING: 1w LED lamps: 1-24
1.5w LED lamps: 1-16
2.3w ring LED lamps: 1-10

DIMMING: Dimmable using minimum 12w and improves with larger load. Use low voltage electronic dimmers only

NOTES: Short Circuit Protection
Constant voltage
Class 2 power unit
For LED lamps only

DIMENSION: 42mm (1.7") x 170mm (6.7") x 33mm (1.3")

DESIGNATION:



SELV-equivalent

LED

Drivers

PRODUCT SPECIFICATION

For additional
assistance, please
contact Bocci:


Vancouver
sales@bocci.ca
www.bocci.ca

Berlin
europe@bocci.ca
www.bocci.ca

© 2019, Bocci Design and Manufacturing Inc. All rights reserved. Any inquiries should be directed to: info@bocci.ca

BOCCI

120/240V LED Driver - 8W



MW-APV-8-12V

PRIMARY: AC 100 - 240V, 300mA, 50/60Hz

SECONDARY: Max. 12V DC (8w max.)

LAMPING: 1w LED lamps: 1-8
1.5w LED lamps: 1-5

DIMMING: **dimnable with dimming module**

DIMMING TYPE: - 10K/N~100K/N Ohms resistance
- 1~10V DC Voltage
- 10V PWM Signal

NOTES: Constant voltage
Class 2 power unit
For LED lamps only

DIMENSION: 30mm (1.2") x 73mm (2.9") x 24mm (0.9")


DESIGNATION: IS 15885(Par 12/Sec13)



SELV-equivalent

ta: 45°C
tc: 75°C

120/240V LED Driver - 16W



MW-APV-16-12V

PRIMARY: AC 100 - 240V, 500mA, 50/60Hz

SECONDARY: Max. 12V DC (16w max.)

LAMPING: 1w LED lamps: 1-16
1.5w LED lamps: 1-10
2.3w ring LED lamps: 1-6

DIMMING: **dimnable with dimming module**

DIMMING TYPE: - 10K/N~100K/N Ohms resistance
- 1~10V DC Voltage
- 10V PWM Signal

NOTES: Constant voltage
Class 2 power unit
For LED lamps only

DIMENSION: 40mm (1.6") x 90mm (3.5") x 29mm (1.1")


DESIGNATION: IS 15885(Par 12/Sec13)



SELV-equivalent

ta: 40°C
tc: 70°C

120/240V LED Driver - 60W



MW-LPF-60D-12

PRIMARY: AC 100 - 240V, 800mA, 50/60Hz
AC 277V, 320mA, 50/60Hz

SECONDARY: Max. 12V DC (60w max.)

LAMPING: 1w LED lamps: 1-60
1.5w LED lamps: 1-40
2.3w ring LED lamps: 1-26

DIMMING: 0-10V dimming
Recommended minimum 10w

DIMMING TYPE: - 10K/N~100K/N Ohms resistance
- 1~10V DC Voltage
- 10V PWM Signal

NOTES: Short Circuit Protection
Constant voltage
Class 2 power unit
For LED lamps only

DIMENSION: 43mm (1.7") x 163mm (6.4") x 32mm (1.3")

DESIGNATION:



ta: 50°C
tc: 80°C



LED

Drivers

PRODUCT SPECIFICATION

For additional
assistance, please
contact Bocci:

Vancouver
sales@bocci.ca
www.bocci.ca

Berlin
europe@bocci.ca
www.bocci.ca

© 2019, Bocci Design and Manufacturing Inc. All rights reserved. Any inquiries should be directed to: info@bocci.ca

BOCCI