



Amicus 16, white washed oak, brushed brass



black powder coat



white powder coat



brushed rose gold



distressed brass



brushed aluminum




Amicus integrated LED top detail

Traveling through Morocco, I was in awe of the skilled craftspeople and their impressive work. I was most enamored with the detail and intricacy of the perforated metal light fixtures. The artistry, patterns, and old-world techniques inspired me and ultimately inspired the Amicus.


Nick Sheridan
Designer




white washed oak
(CM-095)




walnut
(CM-001)




dark stained
walnut (CM-002)



white powder coat
(CM-060)



black powder coat
(CM-049)



brushed aluminum
(CM-012)



brushed rose gold
(CM-046)




brushed brass
(CM-047)



distressed brass
(CM-096)

Amicus 16 pendant



Dimensions: 15.8" Ø, 13.5"
Product weight: 4 lb
Suitable for a sloped ceiling

Integrated LED Specifications

Light Color Options*:
2700 K - 831 Lumens (source)
3500 K - 873 Lumens (source)
Color accuracy: 90+ CRI
Power usage: 10 W
Dimmable (see power options below)
JA8-2019 Compliant

E26 Medium Base Specifications

Lamping: E26 base, 60 W max, G40 recommended
Bulb not included
Input voltage: 250 V AC max

Black Powder Coat (CM-049) low profile round canopy with SVT-3
Cable, Black (CM-039)

Canopy dimensions: 5" Ø, 0.3"

See website for more canopy information
Field adjustable drop length: 0'6" min - 8'0" max
Wood grain will vary
Specifications subject to change
Suitable for dry or damp locations



MATERIAL & FINISH OPTIONS

Amicus 16 part # 06-290-16

Metal Shade

brushed brass (CM-047)
distressed brass (CM-096)
brushed aluminum (CM-012)
brushed rose gold (CM-046)
black powder coat (CM-049)
white powder coat (CM-060)

Wood Top

walnut (CM-001)
dark stained walnut (CM-002)
white washed oak (CM-095)


Lamping*

2700 K LED
3500 K LED
medium base E26 socket

Power Option (LED version only)

120-277 V AC input voltage
TRIAC and ELV dimming

*Available in 3000K, 4000K and other color temperatures upon request



low-profile round canopy
with SVT-3 Cable

