




## **Fixture Type:**

### Catalog Number:

### Project:

### Location:





FM-2111-30

FM-2115-30

## PRODUCT DESCRIPTION

This utilitarian family features a range of sizes to accommodate compact spaces like narrow hallways and stairwell landings as well as medium-sized rooms in office buildings and luxury homes. A thick, one-inch glass shade is pressed and sanded for pure whiteness, while a second insert is layered inside to extract the optimal amount of light from the high-performance LED modules. Available in black and titanium.

### **FEATURES**

- . Durable steel construction with opal glass
- Two layers pressed, sanded glass with additional vacuum formed optical insert inside
- · Can be mounted on wall or ceiling
- No transformer or driver needed
- Dimming: ELV (277V special order)
- Color Temperature: 3000K (2700K/3500K special order)
- CRI: 90
- Rated Life: 54,000 hours

## **SPECIFICATIONS**

Construction: Steel body with opal glass

Light Source: High output LED

Finish: Black, Titanium

Standards: ETL & cETL listed, Damp Location Listed,

IP44 Rated, Title 24 Compliant

### REPLACEMENT GLASS

Part#	Fixture	
RPL-GLA-4109	FM-2109	
RPL-GLA-4111	FM-2111	
RPL-GLA-4115	FM-2115	

# **ORDER NUMBER**

Model		Wattage	Voltage	LED Lumens	Delivered Lumens	Finish		
FM-2109-30	9"	18W		1794	831	ВК	Plack	
FM-2111-30	11"	30W	120V	2759	1193		Black	
FM-2115-30	15"	27W		2729	1380	TT	Titanium	

Example: FM-2115-30-BK

For 2700K special order add a "27" before the finish: **FM-2111-27-TT**For 3500K special order add a "35" before the finish: **FM-2111-35-TT**For 277V special order, add an "F" before the color temperature: **FM-2111F-35-TT**