



	class of insulation	direct mounting	degree of protection	power voltage	attachment	unit weight kg.
9130			IP 20	220-240	E14	0,700
9132			IP 20	120	E12 type B max 28W HALO	0,700
	width	height diffuser	length cable			
	14	14	18±210			
9120			IP 20	220-240	E14	0,950
9121			IP 20	120	E12 type B max 28W HALO	0,950
	width	height	depth			
	14	21	17			
9135 B9135			IP 20	220-240	E14	1,120
U9135 Z9135			IP 20	120	E1 type B max 28W HALO	1,120
	width	height	depth			
	17	32	14			

JJ03 One E14 5W LED light bulb
Cannot be sold separately from 9130 9120 9135
B9135

packaging	quantity	weight (kg)	volume m³	size
9120/9121	1	1,300	0,014	23X29X19
9130/9132	1	1,050	0,014	23X29X19
9135/B9135/U9135/Z9135	1	1,470	0,015	23X41X16

**9120 / 9130 / 9135
sculpted version**

B4/crystal		
AM/amber		
RO/pink		
AZ/light blue		

**9135
sculpted table lamp**

E6/black-crystal		
------------------	--	--



9130 - 9120 - 9138 - B9135



9132 - 9121
U9135

9130 / 9120 / 9135 / B9135

Alternative sources:

E14 max 28W Halo
E14 max 5W Led

Material

Transparent or mass-dyed
thermoplastic technopolymer