moooi

Plié Plissé Light

LUKAS BAZLE



Plié Plissé Light by Lukas Bazle is inspired by the kinetic movements found in nature. This kinetic design has an adjustable cellular pleated shade that lets you choose the intensity and direction of the light. Unfolded, the light is soft and diffused. Perfect for (dinner) parties and lighting your whole room up. Fold the shade in and the lamp shines downwards and more intense, making it easier to work or read a book. As if dancing, Plié Plissé Light moves along with the rhythm of your day.

Detailing



Switch from ambient light to downward lighting with a simple movement.


Colours

White

Plié Plissé Light / Plié Plissé Light 60

Dimensions

60cm | 23.6"



Product

WIDTH 60cm | 23.6"
HEIGHT 38cm | 15"
DEPTH 60cm | 23.6"
DIAMETER 60cm | 23.6"
WEIGHT NETTO 0.7kg | 1.54 | bs

Packaging

width $71 \text{cm} \, | \, 28"$ Height $47 \text{cm} \, | \, 18.5"$ Cubage $0.24 \text{m}^3 \, | \, 8.48 \text{ft}^3$ Length $71 \text{cm} \, | \, 28"$ Weight $6 \text{kg} \, | \, 13.23 \text{lbs}$

Technical CE

MATERIAL

Shade from non-woven PES (Plissé material), coated steel pendant

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPECylinder

INPUT VOLTAGE 220-240

MAX POWER CONSUMPTION

10W

LAMPHOLDER

E27

CABLE LENGTH

250cm | 98.4"

CHROM X 0.41

COLOUR TEMPERATURE

2500 K

All directions

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

- 1

DIAMETER SHADE 60cm | 23.6"

FREQUENCY 50/60

DIMMABLE Yes

CABLE COLOUR

White

CANOPY

Pebble II White, ABS

CHROM Y 0.48 **CRI**

92

LIGHT OUTPUT 700 lm



Technical cULus

MATERIAL

Shade from non-woven PES (Plissé material), coated steel pendant

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

INPUT VOLTAGE 100-120

MAX POWER CONSUMPTION

10W

LAMPHOLDER

E26

CABLE LENGTH

250cm | 98.4"

CHROM X 0.41

COLOUR TEMPERATURE

2500 K

LIGHT DIRECTION All directions

R9

0



LIGHTSOURCE INCLUDED

Yes

DIAMETER SHADE 60cm | 23.6"

FREQUENCY 50/60

DIMMABLE Yes

CABLE COLOUR

White

CANOPY

Pebble II White, ABS

CHROM Y 0.48

CRI 92

LIGHT OUTPUT 700 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is **DIMMER TYPE** compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

Mains dimmable with compatible light source