SWELL SINGLE

DESCRIPTION

Elegant with undulating contours, Swell Single is an LED pendant designed to seamlessly blend the line between indoor and outdoor lighting. Swell single can be suspended individually or as a chandelier grouping to perfectly complement residential, commercial, lounge and hospitality settings alike. Swell is now available in stunning new XL sizes for spaces that demand exceptional scale.

FIXTURE TYPE

Pendant

LIGHT SOURCE

(1) 3000K E26 base 13W PAR30 LED bulb: 1050lm

PRODUCT CODES

Swell Single Narrow (White/Brass):	SWELSNG NRW WHT/BRA
Swell Single Narrow (Black/Brass):	SWELSNG NRW BLK/BRA
Swell Single Narrow (Brass/Brass):	SWELSNG NRW BRA/BRA
Swell Single Medium (White/Brass):	SWELSNG MED WHT/BRA
Swell Single Medium (Black/Brass):	SWELSNG MED BLK/BRA
Swell Single Medium (Brass/Brass):	SWELSNG MED BRA/BRA
Swell Single Wide (White/Brass):	SWELSNG WID WHT/BRA
Swell Single Wide (Black/Brass):	SWELSNG WID BLK/BRA
Swell Single Wide (Brass/Brass):	SWELSNG WID BRA/BRA
Swell Single XL Narrow (White/Brass):	SWELSNG XLNRW WHT/BRA
Swell Single XL Narrow (Black/Brass):	SWELSNG XL NRWBLK/BRA
Swell Single XL Narrow (Brass/Brass):	SWELSNG XLNRWBRA/BRA
Swell Single XL Medium(White/Brass):	SWELSNG XLMED WHT/BRA
Swell Single XL Medium(Black/Brass):	SWELSNG XLMEDBLK/BRA
Swell Single XL Medium(Brass/Brass):	SWELSNG XLMED BRA/BRA
Swell Single XL Wide (White/Brass):	SWELSNG XLWID WHT/BRA
Swell Single XL Wide (Black/Brass):	SWELSNG XL WID BLK/BRA
Swell Single XL Wide (Brass/Brass):	SWELSNG XL WID BRA/BRA



FINISHES



LIGHT CONTROL

Hard-wired, dimmable Compatible with TRIAC/ELV dimmers

FEATURES

Fully dimmable For indoor and outdoor use Damp rated Interchangeable shades

SPECIFICATIONS

Voltage: 120V or 240V 60Hz Power consumption: 13W Color temperature: 3000K Luminosity: 1050 Lumens Luminaire efficacy: 81 Lumens/Watt Color Rendition Index: 82 CRI 40K hour lifespan Cable length: 10' (305cm) Title 20/Title 24 compliant Dark Sky compliant 1 year warranty

CERTIFICATIONS




PACKAGING WEIGHT AND DIMENSIONS


Swell Single:	5.25LBS	15.5" X 16" X 14.5"
	2.4KGS	39cm X 41cm X 37cm

NOTES Custom requests can be considered on volume orders











4.8

(12.25cm)



SWELL XL SINGLE MEDIUM

SWELL XL SINGLE WIDE



DIMENSIONS SWELL SINGLE NARROW

(3.3cm) =

14" (36cm)

1.3″

10' (305cm) MAX

(3.3cm) =

20" (50.8cm)

8″

(20cm)

SWELL XL SINGLE NARROW

4.8

(12.25cm)

12" (30cm)

10' (305cm) MAX

SWELL STRING 3 MIXED

DESCRIPTION

Elegant and infinitely flexible, Swell String is a modular LED lighting system designed to seamlessly blend the line between indoor and outdoor lighting. Swell String's three shade design can be mixed and matched to create dynamic groupings. Swell String can be suspended both vertically and horizontally in configurations of up to (34) lamps from a single power source to perfectly complement residential, commercial, lounge and hospitality settings alike.

FIXTURE TYPE

Pendant

LIGHT SOURCE

(1) 3000K E26 base 13W PAR30 LED bulb: 1050lm

PRODUCT CODES

Swell String Mixed (White/Brass):	SWELSTR MIX WHT/BRA
Swell String Mixed (Black/Brass):	SWELSTR MIX BLK/BRA
Swell String Mixed (Brass/Brass):	SWEL STR MIX BRA/BRA
Swell 12" Extension Cable (White):	SWELSTRACC EXT12 WHT
Swell 12" Extension Cable (Black):	SWELSTRACC EXT 12 BLK
Swell Horizontal Mounting Kit:	SWEL HRZ MOUNT

LIGHT CONTROL

Hard-wired

ELV dimmer recommended

FEATURES

Fully dimmable For indoor and outdoor use Damp rated Interchangeable shades Interconnectable sockets

SPECIFICATIONS

Voltage: 120V or 240V 60Hz Power consumption: 13W Color temperature: 3000K Luminosity: 1050 Lumens Luminaire efficacy: 81 Lumens/Watt Color Rendition Index: 90 CRI 40K hour lifespan (3x) 10' (305cm) vertical mounting kit cable included 30' (915cm) horizontal mounting kit cable sold separately 8' (244cm) power feed cable and canopy included Horizontal mounting kit supports 12 lamps MAX MAX interconnected 14.5W lamps: 34 Title 20/Title 24 compliant Dark Sky compliant 1 year warranty

CERTIFICATIONS





PACKAGING WEIGHT AND DIMENSIONS

Swell String 3 Mixed:	12.3LBS 16.5" X 16" X 14.5	5″
	5.6KGS 42cm X 41cm X	37cm

NOTES

Custom requests can be considered on volume orders






FINISHES





DIMENSIONS

SWELL STRING 3 MIXED VERTICAL



SWELL STRING 3 MIXED HORIZONTAL





Pablo

SWELL STRING SINGLE

DESCRIPTION

Elegant and infinitely flexible, Swell String Single is a modular LED lighting system designed to seamlessly blend the line between indoor and outdoor lighting. Swell String Single allows infinite customization, pick your own collection to create a dramatic and personal grouping to fit any environment. Swell String Single can be suspended both vertically and horizontally in configurations of up to (34) lamps from a single power source to perfectly complement residential, commercial, lounge and hospitality settings alike.

FIXTURE TYPE

Pendant

LIGHT SOURCE

(1) 3000K E26 base 13W PAR30 LED bulb: 1050lm

PRODUCT CODES

Swell String Single Narrow (White/Brass):	SWELSTR SNG NRW WHT/BRA
Swell String Single Narrow (Black/Brass):	SWELSTR SNG NRW BLK/BRA
Swell String Single Narrow (Brass/Brass):	SWELSTR SNG NRW BRA/BRA
Swell String Single Medium (White/Brass):	SWELSTR SNG MED WHT/BRA
Swell String Single Medium (Black/Brass):	SWELSTR SNG MED BLK/BRA
Swell String Single Medium (Brass/Brass):	SWELSTR SNG NRW BRA/BRA
Swell String Single Wide (White/Brass):	SWELSTR SNG WID WHT/BRA
Swell String Single Wide (Black/Brass):	SWELSTR SNG WID BLK/BRA
Swell String Single Wide (Brass/Brass):	SWELSTR SNG NRW BRA/BRA
Swell Power Feed and Canopy (White):	SWELSTR ACC KIT WHT
Swell Power Feed and Canopy (Black):	SWELSTR ACC KIT BLK
Swell 12" Extension Cable (White):	SWELSTRACCEXT12WHT
Swell 12" Extsnsion Cable (Black):	SWELSTR ACC EXT 12 BLK
Swell Horizontal Mounting Kit:	SWEL HRZ MOUNT

LIGHT CONTROL

Hard-wired ELV dimmer recommended

FEATURES

Fully dimmable For indoor and outdoor use Damp rated Interchangeable shades Interconnectable sockets

SPECIFICATIONS

Voltage: 120V or 240V 60Hz Power consumption: 13W Color temperature: 3000K Luminosity: 1050 Lumens Luminaire efficacy: 81 Lumens/Watt Color Rendition Index: 90 CRI 40K hour lifespan (1x) 10' (305cm) vertical mounting kit cable included 30' (915cm) horizontal mounting kit cable sold separately 8' (244cm) power feed cable and canopy sold separately Horizontal mounting kit supports 12 lamps MAX MAX interconnected 14.5W lamps: 34 Title 20/Title 24 compliant Dark Sky compliant

1 year warranty

CERTIFICATIONS



PACKAGING WEIGHT AND DIMENSIONS

 Swell String Single:
 5.25LBS
 15.5" X 16" X 14.5"

 2.4KGS
 39cm X 41cm X 37cm

NOTES

Custom requests can be considered on volume orders










DIMENSIONS

SWELL STRING SINGLE NARROW SWELL STRING SINGLE MEDIUM SWELL STRING SINGLE WIDE








POWER FEED CABLE







CANOPY





SWELL CHANDELIER

DESCRIPTION

Elegant with undulating contours, Swell Chandelier is an LED chandelier designed to seamlessly blend the line between indoor and outdoor lighting. Swell Chandelier is available in groupings of 3 and 6 lamps, creating a dramatic and personal grouping to fit any environment.

FIXTURE TYPE

Pendant

LIGHT SOURCE

(1) 3000K E26 base 13W PAR30 LED bulb: 1050lm per lamp

PRODUCT CODES

Swell Single Narrow (White/Brass):	SWELSNG NRW WHT/BRA
Swell Single Narrow (Black/Brass):	SWELSNG NRW BLK/BRA
Swell Single Narrow (Brass/Brass):	SWELSNG NRW BRA/BRA
Swell Single Medium (White/Brass):	SWELSNG MED WHT/BRA
Swell Single Medium (Black/Brass):	SWELSNG MED BLK/BRA
Swell Single Medium (Brass/Brass):	SWELSNG MED BRA/BRA
Swell Single Wide (White/Brass):	SWELSNG WID WHT/BRA
Swell Single Wide (Black/Brass):	SWELSNG WID BLK/BRA
Swell Single Wide (Brass/Brass):	SWELSNG WID BRA/BRA
17" Chandelier Canopy:	CHND CAN 17
26" Chandelier Canopy:	CHND CAN 26






FINISHES







DIMENSIONS







CHANDELIER CANOPY 26"



LIGHT CONTROL Hard-wired

ELV dimmer recommended

FEATURES

Fully dimmable For indoor and outdoor use Damp rated Interchangeable shades

SPECIFICATIONS

Voltage: 120V or 240V 60Hz Power consumption: 13W per lamp Color temperature: 3000K Luminosity: 1050 Lumens per lamp Luminaire efficacy: 81 Lumens/Watt Color Rendition Index: 90 CRI 40K hour lifespan Cable length: 10' (305cm) Title 20/Title 24 compliant Dark Sky compliant 1 year warranty

CERTIFICATIONS



PACKAGING WEIGHT AND DIMENSIONS

CE

Swell Single:	5.25LBS 15.5" X 16" X 14.5"
	2.4KGS 39cm X 41cm X 37cm
Chandelier canopy 26":	30LBS 32" X 32" X 6"
	13.6KGS 81cm X 81cm X 15cm
Chandelier canopy 17":	15LBS 22" X 22" X 6"
	6.8KGS 56cm X 56cm X 15cm

NOTES

Custom requests can be considered on volume orders





