

t-3212 / t-3212A / t-3213 / t-3213A
493032121


Plafón de aluminio con vidrio óptico blanco satinado.

Aluminum flushmount. White satin glass.



960°

IP
20



Rev. May. 2012

LE RECOMENDAMOS LEA LAS INSTRUCCIONES ANTES DE PROCEDER A LA INSTALACIÓN.

GUARDE LAS INSTRUCCIONES PARA FUTURAS REFERENCIAS.

* Asegúrese de que la corriente está desconectada antes de conectar el aparato.

* El montaje de luminarias debe ser efectuado solamente por personal técnico.

* No utilizar bombillas con potencia superior a la indicada en la etiqueta.

* Únicamente para uso en interiores.

* Para limpieza no utilizar alcohol ni disolventes

* Recomendamos la intervención de 2 personas para el montaje de la lámpara

WE RECOMMEND TO READ THE INSTRUCTIONS ENTIRELY BEFORE STARTING YOUR INSTALLATION.

PLEASE SAVE THESE INSTRUCTIONS SO THAT YOU CAN REFER TO THEM A LETER TIME.

* Make sure the power has been disconnected before installing the fixture.

* Lighting fixtures should be installed only by qualified personnel.

* Make sure the bulb never exceeds the maximum wattage especified on the fixture label.

* For indoor use only.

* Do not use alcohol or solvents to clean the lamp


* For your convenience assembly by two people ist recommended..

Instrucciones / Assembly instructions

1- Desenroscar los tornillos laterales del tapapared (A). Liberar la sujeción (B). Figura 1.

1- Unscrew the lateral screws (A) to remove the canopy (A) from the mounting bracket (B). Figure 1.


1



2- Introducir el cable de red por el agujero central de la sujeción (B). Atornillar la sujeción (B) al techo. Figura 2.

2- Insert the electrical wires from the outlet box into the mounting bracket through the central hole. Affix the mounting bracket (B) to the ceiling. Figure 2.


2



3- Desenroscar y liberar las tuercas grafiladas y arandelas (C) y la tuerca grafilada y la arandela(D) dos tuercas en el modelo t-3213-. Figura 3.

3- Untighten and remove the knurled nuts and washers (C) and the knurled nut and whaser (D) two nuts in case of the model t-3213-. Figure 3.

3




Instrucciones / Assembly instructions

4- Colocar las bombillas. Colocar la tapa superior [F]. Enroscar de nuevo las tuercas grafiladas y arandelas [C] y [D] liberadas previamente. Figura 4.

4- Insert the bulbs. Place the top plate [F]. Tighten the knurled nuts and washers [C] and [D] removed previously. Figure 4.


4




5- Realizar las conexiones eléctricas mediante los conectores suministrados. Acoplar el plafón a la sujeción [B]. Enroscar los tres tornillos [A]. Figura 5.

5- Connect the electrical wires using the wire connector provided. Affix the fixture to the mounting bracket [B]. Screw the lateral screws [A] removed previously. Figure 5.

5



5.1



6- Para cambiar las bombillas: liberar la/s tuerca/s grafilada y la arandela [D] aguantando la lámpara [E] para evitar una caída brusca. Figura 6.

6- To rebulb: remove the knurled nut/s [D] and whaser/s holding the fixture to avoid the lamp falling down abruptly. Figure 6.

6

