

Modern, crisp lines and a slim profile combine in the handsome Windfall LED outdoor fixture. Indirect light bounces off the smooth, matte finish of the back plate to create a gentle glow for way-finding in outdoor corridors and walkways.

Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

SPECIFICATIONS

DELIVERED LUMENS	1680	
WATTS	20	
VOLTAGE	120V, 277V	
DIMMING	ELV	
LIGHT DISTRIBUTION	Symmetric	
MOUNTING OPTIONS	Wall	
ССТ	3000K	
CRI	80	
COLOR BINNING	3-Step	
BUG RATING	N/A	
DARK SKY	Non-compliant	
WET LISTED	IP65	
GENERAL LISTING	ETL, ADA	
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.	
START TEMP	-30°C	
FIELD SERVICEABLE LED	Yes	
CONSTRUCTION	Aluminum	
HARDWARE	Stainless Steel	
FINISH	Powder Coat	
LED LIFETIME	L70; 70,000 hours	
WARRANTY*	5 years	
WEIGHT	5 lbs.	

^{*} Visit techlighting.com for specific warranty limitations and details.






WINDFALL shown in silver

ORDERING INFORMATION

700OWWND	FINISH	LAMP
	B BLACK I SILVER	LED LED 80CRI, 3000K, 120V LED277 LED 80CRI, 3000K, 277V




Windfall

PHOTOMETRICS*

*For latest photometrics, please visit www. techlighting.com/OUTDOOR

WINDFALL

Total Lumen Output: 1680
Total Power: 20
Luminaire Efficacy: 84
Color Temp: 3000K
CRI: 80
BUG Rating: N/A



PROJECT INFO

FIXTURE TYPE & QUANTITY

JOB NAME & INFO

NOTES



GENERATION BRANDS 7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

